



FLR.0184 STUCCO BALCONY

Two-component cement surfacer,
waterproof, high adherence

✘ Customs Code

3214 9000

⚖ Dosage

0.5 kg /m²

📦 Packaging

- Pail 4 kg [A]
- Bucket 0.8 kg [A]
- Bottle 1 kg [B]
- Bucket 0.2 kg [B]
- Kit: 1 Pail 4 kg [A] + 1 Bottle 1 kg [B]
- Kit: 1 Bucket 0.8 kg [A] + 1 Bucket 0.2 kg [B]

🔪 Application

- Spatula
- Apply by hand
- Sponge float
- Sponge



www.azichem.com

Updated: 24/02/2018

General sales conditions and legal notices on

www.azichem.com/disclaimer

Page: 1/2

Family
Floortech

Product Lines

- Aqua
- Building

Components
Two-components

Type
Adhesive and putty for flooring

Functional Categories

- Bonding and filling tiles, parquet, etc.
- Transparent waterproofing of tiled terraces and balconies

Appearance
Powder + Liquid

General description

Two-component cement surfacer, fine, fluid plastic consistency, for plugging gaps between tiles, and to fill and joint static cracks, micro- and macro-cavities etc., prior to applying PROTECH BALCONY in non-pellicular transparent waterproofing interventions of terraces and balconies.

Fields of application

Specific putty for the preliminary preparation of supports (open gaps, micro and macro-cavities and fissures) for the subsequent application of PROTECH BALCONY on terraces and balconies.

Available colours

- Light gray

Basic features

- ↔ Max. recommended thickness: 6 mm
- ⊘ Maximum diameter of aggregate: 0.35 mm
- 🔥 Nonflammable
- 🕒 Pot-life: 15 - 20 min
- 🕒 Shelf-life: 12 months
- 🌡 Temperature of use: +5 / +35 °C
- 🧤 Use wearing protective gloves
- ☀ UV-resistant

Technical specifications

Capillary absorption (UNI EN 13057): 0.10 kg•h^{0.5}/m²

Complete hardening (a 20°C): 180 min

Mixing ratio of the components A:B: 4:1 _

Tools cleansing

- Water

Applicable on

- Tiles

Instructions for use

Add the quantity of component B required to obtain the desired consistency to component A; mix thoroughly until a homogeneous lump-free mixture is obtained. Place on site using a spatula, sponge float or simply with the fingers of the hand (wearing a rubber glove).

it is possible to correct the consistency, where necessary, by adding moderate quantities of water to the ready mixture.

In the cases of coloured surfacings, it is recommended to mix the two-component with small amounts of coloured pigments that can be purchased at any paint shop.

Substrate preparation

Application surfaces should be clean, free of soiling, crumbling and non-adhering parts, dust, etc., conveniently saturated with water until they reach the condition "saturated with dry surface".

Storage and preservation

Protect from freezing. Store the product in its original packing, in a fresh and dry environment, avoiding frost and direct sunlight. Inadequate storage of the product may result in a loss of rheological performance. Store the product at a temperature between +5°C and +35°C.



Warnings, Precautions and Ecology

Technical and performance data outlined in this document are the result of laboratory testing conducted in a conditioned environment, as such they can result as considerably changed from operating and application conditions. The need follows to carry out preliminary tests in actual use conditions.

The user is required to check the product's most recent Material Safety Data Sheet, reporting physical-chemical and toxicological data, risk phrases and other useful information on how to safely transport, use and dispose of the product and its packaging. It is also reminded that the product and its packaging must not be dispersed in the environment for any reason.

Do not apply in case of direct exposure to sunlight. Cure the prolonged moist hardening of exposed surfaces.

Given the high adherence and rapid drying of the product, it is advisable to wash the excess parts of the surfacings immediately after application, with a sponge impregnated with water, ("smudges") to avoid tedious cleaning

In transparent non-pellicular waterproofing interventions of terraces and balconies, STUCCO BALCONY must only be applied to restore the continuity of labile, detached or missing puttying. For this reason, the consumption is extremely variable from case to case, depending on the actual volume of filling to be performed.

STUCCO BALCONY is produced/distributed by



Via Giovanni Gentile, 16/A - 46044 Goito (MN), Italy
info@azichem.com Tel. +39 0376.604185 /604365 Fax +39 0376 604398



www.azichem.com

Updated: **24/02/2018**
General sales conditions and legal notices on
www.azichem.com/disclaimer