



OSM.0087

OSMOCEM QUICK

Cement compound for
immediately stopping the
infiltration of water

✘ Customs Code

3816.0000

⚖ Dosage

1.75 kg /dm³

📦 Packaging

- Pail 5 kg
- Bag 25 kg
- Pallet: 150 x (Pail 5 kg)
- Pallet: 50 x (Bag 25 kg)

🔪 Application

- Apply by hand
- Spatula

Family
Osmocem

Product Lines

- Aqua
- Building
- Infratech

Components
Single-component

Type

Quick-setting waterproofing osmotic compounds

Functional Categories

- **Osmotic waterproofing**
- **Instantaneous stoppage of water infiltrations in buildings**
- **Structural maintenance of dams, reservoirs, ducts and water ducts**
- **Structural maintenance of tunnels**

Appearance
Powder

General description

Cement compound for instantaneously stopping water leaks in underground rooms or structures out of the ground, even in the presence of moderate negative thrust pressure. Based on rapid hardening and high resistance hydraulic binders and special additives, it hardens in 30" - 60", stopping the water flow.

Fields of application

Immediate stop to water infiltration in building structures: • Gray
tubs, tanks, cellars, elevator shafts, pipes, masonry
underground etc.

Available colours

Basic features

∅ Diameter:
0.4 mm

↔ Max. recommended thickness:
15 cm

➔➔ Min. recommended thickness:
5 cm

🔥 Nonflammable

🕒 Pot-life:
60 s

🕒 Shelf-life:
6 months

🧴 Solvent-free

🌡 Temperature of use:
+5 / +35 °C

👁 Use wearing protective glasses

🧤 Use wearing protective gloves

Technical specifications

Complete hardening (a 20°C): 180 s

Tools cleansing

- Water

Applicable on

- Concrete
- Bricks
- Mixed walls (bricks and stones)
- Stone walls
- Rock walls

Instructions for use

Mix with water, if possible at a temperature not less than 20 °C, no more than 250 cc per kg of product. The product reacts immediately and it is very quick, then mix from time to time the quantities of product strictly necessary and immediately applicable.

Apply the product on site by hand exclusively and immediately after mixing the product with water while wearing protective rubber gloves.

Where necessary, in case of pressure infiltrations, proceed with the installation of drainage with a plastic tube, with small diameter, initially sealing sections adjacent to the drainage and then, once you stop the infiltration, sealing the drainage itself.



www.azichem.com

Updated: **14/03/2018**

General sales conditions and legal
notices on

www.azichem.com/disclaimer

Substrate preparation

Thoroughly clean the contact surfaces. In the case of cracks, discontinuities, cavities, etc. preliminarily prepare application sections countersinking towards the inside of the masonry, according to the "dovetail" shape (in order to facilitate the hydraulic sealing of the intervention).

Storage and preservation

Store the product in its original packing, in a fresh and dry environment, avoiding frost and direct sunlight. Inadequate storage of the product may result in a loss of rheological performance. Protect from humidity.



Warnings, Precautions and Ecology

Technical and performance data outlined in this document are the result of laboratory testing conducted in a conditioned environment, as such they can result as considerably changed from operating and application conditions. The need follows to carry out preliminary tests in actual use conditions.

The user is required to check the product's most recent Material Safety Data Sheet, reporting physical-chemical and toxicological data, risk phrases and other useful information on how to safely transport, use and dispose of the product and its packaging. It is also reminded that the product and its packaging must not be dispersed in the environment for any reason.

It is a caustic product: wear enveloping thick rubber protective gloves; in case of contact, wash with copious amounts of water. Do not stir the product in the hardening phase and do not float it when it has just been laid.

It is always essential to carry out preliminary tests to check the appropriateness of the product, depending on specific requirements.

OSMOCEM QUICK is produced/distributed by



Via Giovanni Gentile, 16/A - 46044 Goito (MN), Italy
info@azichem.com Tel. +39 0376.604185 /604365 Fax +39 0376 604398



www.azichem.com

Updated: **14/03/2018**
General sales conditions and legal notices on
www.azichem.com/disclaimer