



CSX.0245

CONSILEX SMOG REMOVER

Specific cleaner for the removal of smog and graffiti from walls

Customs Code

3402 9010

Packaging

- Plastic can 5 kg
- Plastic can 25 kg

Application

- Brush
- Paint roller

Family
Consilex

Product Lines

- Building
- Opus
- Sanageb

Components
Single-component

Type
Soot clening treatments based on tensioactive agents

Functional Categories

- Roads and municipal maintenance interventions
- Deep cleaning of supports

Appearance
Liquid

General description

CONSILEX SMOG REMOVER is an innovative product, designed for cleaning blackened external walls, especially encrusted by soot from pollution and smog, graffiti. It is perfect for cleaning outside walls, external walls and roofs made of natural stone, exposed brickwork, reconstituted stone, concrete, etc.

General features

It is composed of special thickened surfactants, CONSILEX SMOG REMOVER offers considerable advantages in terms of ease of application, safety and effectiveness, in contrast to generally used corrosive products. In the form of homogeneous gel, it can very easily be applied by brushing, without leaking. It does not contain soda and potassium, and does not need neutralisation after rinsing.


Dosage


Approximately 0,30 kg of CONSILEX SMOG REMOVER for every square metre of surface to be treated.


Fields of application

Removal of graffiti and blackish incrustations produced by smog and soot deposits from the external walls of buildings and monuments and on all civil and industrial buildings.


Basic features

 Density:
0.85 kg/dm³

 Pot-life:
20 min


 Solvent-free

 Use wearing protective glasses

 Available colours
Beige

 Nonflammable

 Shelf-life:
12 months

 Temperature of use:
+5/+30 °C

 Use wearing protective gloves

Technical specifications

Boiling point/range: 100 °C

Not to be diluted

The product creates film

IF YOU WANT TO SOLVE IT
 **azichem**

www.azichem.com

Updated: **24/08/2020**

General sales conditions and legal notices on

www.azichem.com/disclaimer

Tools cleansing

- Water

Applicable on

- Plasters
- Concrete
- Bricks
- Tuff
- Mixed walls (bricks and stones)
- Stone walls
- Rock walls

Substrate preparation

Application support must be dry.

Instructions for use

The product is for use in its pure state, without diluting. Shake the package prior to use and carry out preliminary tests on a small portion of the surface before use.

Apply the product by brushing on the support to be treated for about 300 g/m² (variable depending on the type and porosity of the substrate). Then leave to work for about 30-60 minutes. Avoid letting the product dry completely on the support. Once the time required to ensure that the active ingredients have performed their cleaning action has passed, remove the product from the support with a 150 bar pressure washer.

For perfect application, CONSILEX SMOG REMOVER should be used when the temperature of the supports is between 5°C and 30°C. Do not use in case of rain, or very high temperatures (above 35°C).

Do not dilute or mix with other products. Do not apply on wet media. Do not apply on painted media, without carrying out accurate preliminary tests; some paints may indeed be damaged by applying the product.

Under normal conditions of use, which provide adequate ventilation, it is not necessary to use protective respiratory devices; wear protective masks in closed environments or with poor ventilation. Wear rubber gloves and safety glasses when handling the product.

Storage and preservation

Protect from freezing. Store the product in its original packing, in a fresh and dry environment, avoiding frost and direct sunlight. Inadequate storage of the product may result in a loss of rheological performance. Protect from humidity. Store the product at a temperature between +5°C and +35°C.



Warnings, Precautions and Ecology

The general information, along with any instructions and recommendations for use of this product, including in this data sheet and eventually provided verbally or in writing, correspond to the present state of our scientific and practical knowledge.

Any technical and performance data reported is the result of laboratory tests conducted in a controlled environment and thus may be subject to modification in relation to the actual conditions of implementation.

Azichem Srl does not assume any liability arising from inadequate characteristics related to improper use of the product or connected to defects arising from factors or elements unrelated to the quality of the product, including improper storage.

Those wishing to utilise the product are required to determine prior to use whether or not the same is suitable for the intended use, assuming all consequent responsibility.

The technical and characteristic details contained in this data sheet shall be updated periodically. For consultation in real time, please visit the website: www.azichem.com. The date of revision is indicated in the space to the side. The current edition cancels out and replaces any previous version.

Please note that the user is required to read the latest Safety Data Sheet for this product, containing chemical-physical and toxicological data, risk phrases and other information regarding the safe transport, use and disposal of the product and its packaging. For consultation, please visit: www.azichem.com.

It is forbidden to dispose of the product and/or packaging in the environment.

CONSILEX SMOG REMOVER is produced/distributed by



Via Giovanni Gentile, 16/A - 46044 Goito (MN), Italy
info@azichem.com Tel. +39 0376.604185 /604365 Fax +39 0376 604398



www.azichem.com

Updated: **24/08/2020**
General sales conditions and legal
notices on
www.azichem.com/disclaimer