



Family
Proseal

Type
Butt-straps, bars and plastic profiles

Product Lines
• Aqua
• Building
• Infratech

Functional Categories
• Osmotic waterproofing
• Waterproofing with hot-sprayed elastomeric coatings (100% pure polyurea)
• Waterproofing control joints or construction joints
• Horizontal cement waterproofing of terraces and balconies

Components
Single-component

Appearance
Tape

PRS.0092

PROBAND

Butyl rubber-based self-adhesive waterproofing strap

Customs Code

3919 1015

Packaging

- Roll 10 m

Application

- Apply by hand

General description

Cold applied water-repellent adhesive tape, composed of a layer with visco-elastic butyl rubber consistency, coated with a polypropylene non-woven fabric, for elastic waterproofing of non-structural joints in balconies, terraces, etc. Size of the strap: 80 mm x 0.9 mm.

General features

The PROBAND non-woven fabric coating is composed of 100% pure polypropylene fibres, with a weight of 30 g/m² and a tensile strength of 45 N.

Dosage

1.1 m/m: 1 metre of PROBAND for each linear metre, being careful to overlap the rolls of approximately 5-10 cm in correspondence with the edges of the band.

Fields of application


Elastic waterproofing of non-structural joints in balconies and terraces, especially in the protective "kerb" of the connection joints between the screed and the vertical wall.

Basic features

 Nonflammable


 Shelf-life:
12 months


 Solvent-free

 Temperature of use:
+5 / +40 °C

 Use wearing protective gloves

 UV-resistant

 Width:
8 cm

 Available colours
Gray

Technical specifications

Unit weight: 30 g/m²

Working temperature: -30 / +80 °C



www.azichem.com

Updated: 11/09/2019

General sales conditions and legal notices on

www.azichem.com/disclaimer

Page: 1/2

Substrate preparation

The application supports must be clean, dry, undamaged, cohesive, free from fouling and dust.

Instructions for use

The strap is provided with a special waxed paper film on the adhesive side. To apply, proceed with the detachment of the protective film and place the strap in its final place, with the adhesive side facing the support. Apply slight pressure with your hand to ensure proper adhesion to the support. Then continue to detach the protective film while unwinding of the roll and setting on site, taking care to avoid the formation of bubbles.

Storage and preservation

Store the product in its original packing, in a fresh and dry environment, avoiding frost and direct sunlight. Store the product at a temperature between +5°C and +35°C.



Warnings, Precautions and Ecology

Technical and performance data outlined in this document are the result of laboratory testing conducted in a conditioned environment, as such they can result as considerably changed from operating and application conditions. The need follows to carry out preliminary tests in actual use conditions.

The user is required to check the product's most recent Material Safety Data Sheet, reporting physical-chemical and toxicological data, risk phrases and other useful information on how to safely transport, use and dispose of the product and its packaging. It is also reminded that the product and its packaging must not be dispersed in the environment for any reason.

Butyl mastics are extremely sensitive to the action of solvents.

It is recommended to coat PROBAND, once placed, with elasto-plastic cement mortars or similar products (OSMOCEM FLEX, OSMOCEM D, SYNTECH POLYUREA SPRAY 400).

PROBAND is produced/distributed by



Via Giovanni Gentile, 16/A - 46044 Goito (MN), Italy
info@azichem.com Tel. +39 0376.604185 /604365 Fax +39 0376 604398



www.azichem.com

Updated: **11/09/2019**
General sales conditions and legal
notices on
www.azichem.com/disclaimer